

MARINE GENERATOR SPECIFICATIONS



Generator Model*		kW†	Hz	Cylinder	RPM	Phase	Voltage	Amps	Length x Width x Height mm (in) U – Unhoused / R – Radiator	Weight (Wet) kg (lb)			
DIESEL	40EOZCJ	40	60	4	1800	3	120 / 208	139	U – 1524 (60) x 722 (28.4) x 960 (37.8) R – 1858 (73.2) x 827 (32.6) x 1265 (49.8)	U – 935 (2060) R – 957 (2110)†			
						1	120 / 240	120					
						3	120 / 240	150					
						3	127 / 220	131					
						3	139 / 240	120					
	33EFOZCJ	33	50		1500	3	277 / 480	60					
						3	110 / 190	125					
						3	110 / 220	108					
						1	115 / 230	143					
						3	220 / 380	63					
	40EFOZCJ	40	50	4	1500	3	230 / 400	60	U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	U – 971 (2140) R – 993 (2190)†			
						3	240 / 416	57					
						3	110 / 190	152					
						1	110 / 220	131					
						1	115 / 230	174					
	50EFOZCJ	50	50		1500	3	220 / 380	76					
						3	230 / 400	72					
						3	240 / 416	69					
						3	110 / 190	190			U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	U – 1005 (2216) R – 1028 (2266)†	
						1	110 / 220	164					
	55EOZCJ	55	60	4	1800	1	115 / 230	196					
						3	220 / 380	95					
						3	230 / 400	90					
						3	240 / 416	87					
						3	120 / 208	191	U – 1549 (60.9) x 738 (29) x 961 (37.8) R – 1884 (74.2) x 827 (32.5) x 1265 (49.8)	U – 982 (2164) R – 1004 (2214)†			
	45EFOZCJ	45	50		1500	1	120 / 240	165					
						1	120 / 240	221					
						3	127 / 220	180					
						3	139 / 240	165					
	65EOZCJ	65	60		1800	3	277 / 480	83					
						3	110 / 190	171					
						3	110 / 220	148					
						1	115 / 230	196					
						3	220 / 380	86					
	55EFOZCJ	55	50		1500	3	230 / 400	79	U – 1606 (63.2) x 738 (29) x 961 (37.8) R – 1941 (76.4) x 827 (32.5) x 1265 (49.8)	U – 1016 (2240) R – 1039 (2290)†			
						3	240 / 416	71					
						3	120 / 208	226					
						1	120 / 240	195					
						1	120 / 240	221					
	80EOZCJ	80	60	4	1800	3	127 / 220	213					
						3	139 / 240	195					
						3	277 / 480	98					
						3	110 / 190	209					
						3	110 / 220	181					
	70EFOZCJ	70	50		1500	1	115 / 230	217					
						3	220 / 380	105					
						3	230 / 400	95					
						3	240 / 416	89					
						3	120 / 208	278	U – 1657 (65.2) x 753 (29.6) x 999 (39.3) R – 1992 (78.4) x 890 (35) x 1277 (50.3)	U – 1148 (2530) R – 1179 (2600)†			
	99EOZCJ	99	60		1800	3	120 / 240	241					
						3	127 / 220	262					
						3	139 / 240	241					
						3	277 / 480	120					
	80EFOZCJ	80	50		1500	3	110 / 190	266					
						3	110 / 220	230					
						3	220 / 380	133					
						3	230 / 400	126					
						3	240 / 416	121					
	125EOZCJ	125	60	6	1800	3	120 / 208	343	U – 1732 (68.2) x 753 (29.6) x 999 (39.3) R – 2067 (81.3) x 890 (35) x 1277 (50.3)	U – 1243 (2740) R – 1275 (2810)†			
						3	120 / 240	298					
						3	127 / 220	325					
						3	139 / 240	298					
						3	277 / 480	149					
	100EFOZCJ	100	50		1500	3	110 / 190	304					
						3	110 / 220	262					
						3	220 / 380	152					
						3	230 / 400	144					
						3	240 / 416	139					
	150EOZCJ	150	60		1800	3	120 / 208	520	U – 2068 (81.4) x 893 (35.2) x 1003 (39.5) R – 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	U – 1515 (3340) R – 1578 (3478)†			
						3	120 / 240	451					
						3	127 / 220	492					
						3	139 / 240	451					
						3	277 / 480	226					
	125EFOZCJ	125	50		1500	3	110 / 190	474					
						3	120 / 208	433					
						3	110 / 220	409					
						3	220 / 380	237					
						3	230 / 400	225					
	200EOZCJ	200	60	6	1800	3	240 / 416	217	U – 2091 (82.3) x 893 (35.2) x 1003 (39.5) R – 2498 (98) x 970 (38.2) x 1086 (42.8)	U – 1551 (3419) R – 1613 (3557)†			
						3	120 / 208	695					
						3	120 / 240	602					
						3	127 / 220	657					
						3	139 / 240	602					
	175EFOZCJ	175	50		1500	3	277 / 480	301					
						3	110 / 190	666					
						3	110 / 220	575					
						3	220 / 380	333					
						3	230 / 400	316					
							3	240 / 416	304				